

Industrial Rigger Safety Boots

Model: H-9437 | OilShield Pro



Toe Cap
Protection



Anti
Penetration



Fuel Oil
Resistant



Slip
Resistance



Anti
Static



Scuff Cap
Protection

Technical Specifications

Upper	Full Grain Crazy Horse Cow Leather
Lining	Bactivoid™ Breathable Sandwich Mesh
Insole	Anti-Fatigue Memory Foam Insole
Outsole	PU / Nitrile Rubber Outsole
Toe Cap	VortiGard™ Composite Toe Cap (200J)
Midsole	FlexBarrier™ Puncture Protection (1100N)
Size Range	EU 36–49 UK 2–15 US 3–16
Height	Approx. 31cm (EU42)

Certifications & Standards

	EN ISO 20345:2022+A1:2024 S3S SR CI HI FO HRO
	ASTM F2413-24 I/C PR SD100
	CSA Z195:14

Performance Notes

- **SR:** Slip Resistance Tested on Ceramic Tile with Glycerol
- **Anti-Static:** Electrical Resistance 100kΩ–1000MΩ
- **HRO:** Heat Resistant Outsole up to 300° C



VortiGard™ Composite Toe Cap (200J)
Non-metallic Protection
Against Impact Hazards.



FlexBarrier™ Puncture Protection (1100N)
Flexible Penetration Protection
with Lightweight Comfort.



Heavy-Duty Industrial Outsole
Excellent Grip, Abrasion Resistance
and Fuel Oil Resistance.

Recommended Applications:




Oil & Gas



Heavy
Industry



Outdoor
Work



Manufacturing



Construction



Industrial
Maintenance



Scan for
More Information

www.safetoe.net