



# L-7196 **White**

## Water & Slip Resistant Work Shoes

Upper : Water Resistant Micro Fiber Leather

Lining : BactiVoid™ Breathable Sandwich Mesh

Insole : Soft Hi-Polyu Insoles

Outsole : Flexible PU Injection

Toecap : VortiGard™ Steel Toecap

Size : EU 37-47#, UK 3-13#, US4-14#

CE EN ISO 20345:2011 S2 SRC

ASTM E 2149-2020 Approved Anti-bacteria Lining & Insole (Odor Resistant)

Application : Kitchen, Healthcare, Food Industry, Cleaning Industry, Laboratory Research, Food Storage etc



200 JOULE  
TOECAP



SLIP-  
RESISTANT



SHOCK  
ABSORPTION



ANTI-STATIC



PETROL AND  
CHEMICAL  
RESISTANT



WATER  
RESISTANT



OIL  
RESISTANT



EXTRA  
WIDE


### VortiGard™ Steel Toecap Protection • **EN ISO 20345:2011**

Stainless Steel Toecap is heavy duty and corrosion resistant. The impact resistance can reach 200 joules from falling or rolling objects. The compression resistance can reach 15kN.



### PneumaTex™ Micro Fiber Leather • **EN ISO 20345:2011**

High quality micro fiber leather with thickness 1.6-1.8mm. It is treated with water resistant coating to keep feet dry from raining workday. The tear strength of upper leather can reach to 120 Newtons.



### BactiVoid™ Sandwich Air Mesh • **EN ISO 20345:2011**

Honeycomb design sandwich air mesh lining is breathable & abrasion resistant. It can keep user's feet dry all days. The abrasion resistant can reach more than 51200 cycles at dry test. Meanwhile, the mesh is treated with anti-bacteria from Sweat, which is Odor Resistant.




### Flexible PU Outsole • **EN ISO 20345:2011**

PU outsoles are manufactured with Germany Fully Automatic Injection Technology. The whole outsole is soft and shock absorption. The outsole can pass SRC slip-resistant test.

## Sole Bonding Strength Test

- EN ISO 20345:2022 (Between Upper & Sole)
- Average Test Result  $5.8 \pm 5$  (N/mm)



### Upper, Lining & Bonding Strength Test Result

|                                   |                        |
|-----------------------------------|------------------------|
| Leather Tear Strength $\geq$      | 120.0 Newtons          |
| Leather Tensile Properties $\geq$ | 15.0 N/mm <sup>2</sup> |
| Lining Tear Strength $\geq$       | 15.0 N/mm              |
| Bonding Strength $\geq$           | 4.0 N/mm               |

| ✓ Protection With Slip Resistant (SR)                                                                                |  | Result                                                       |
|----------------------------------------------------------------------------------------------------------------------|--|--------------------------------------------------------------|
| Test Requirement : Forward Heel Slip $\geq 0.31$ (ISO 13287:2019)<br>Backward Heel Slip $\geq 0.36$ (ISO 13287:2019) |  | PASS                                                         |
| Standards : EN ISO 20342:2022(5.3.5) , Test floor: Ceramic tile, Lubricant: Sodium lauryl sulphate                   |  |                                                              |
| ✓ Protection With Anti-Static                                                                                        |  | Result                                                       |
| Test Requirement : Anti-static 100K $\Omega$ -1000M $\Omega$ , Test Voltage: 100 $\pm$ 2 V DC, Test Period: 1 Minute |  | PASS                                                         |
| Standards : EN ISO 20345:2022 (6.2.2.2) Dry Humidity (30 $\pm$ 5) & Wet Humidity (85 $\pm$ 5)                        |  |                                                              |
| ✓ Protection Resistant to Fuel Oil                                                                                   |  | Result                                                       |
| Test Requirement : Change in Volume and Change in Hardness (Outsole) is No More Than +12%(*)                         |  | PASS                                                         |
| Standards : EN ISO 20345:2022 (6.4.2)                                                                                |  |                                                              |
| SAFETOE Standard Package Instruction (Average 42# for Reference)                                                     |  |                                                              |
| Shoes Weight : 1.0-1.1 KGS /Pair                                                                                     |  | Carton Weight : 11-12 KGS /Carton                            |
| 1 Pair / Color Box , Dimensions : 32 $\times$ 21 $\times$ 12CM                                                       |  | 10 Pair / Carton , Dimensions : 62 $\times$ 43 $\times$ 33CM |



### User Instructions:

- 1.) RECOMMENDED TO USE : Kitchen, Healthcare, Food Industry, Cleaning Industry, Laboratory Research, Food Storage etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on tongue label. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size.

Footwear which are too loose or too tight may not provide optimum level of protection.

- 4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.
- 5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.