



## Industrial Grade Wellington Boots | CE S5 Certified

### W-6038 S5 (AquaShield)

Upper : Waterproof PVC (Thickness: 1.8±0.2mm)  
 Lining : Breathable Mesh Fabric (Quick-Dry)  
 Insoles: Removable EVA with Arch Support  
 Outsole : Nitrile-Enhanced PVC Lug Design  
 Slope Angle: 38° for Mud Shedding  
 Toecap : VortiGard™ Steel Toecap (200J Impact)  
 Penetration : VortiGard™ Steel Midsole Plate (1100N Puncture)  
 Certification: EN ISO 20345:2022 S5 SR (NB:2443)  
 Height : 38.5cm / 15 inch (Size 42# for reference)  
 Size : EU 37-47#, UK 3-13#, US4-14#  
 Application : Construction, Chemical, Food Industry, Catering, Cleaning, Farm & Garden, Food Storage etc




#### VortiGard™ Steel Toecap Protection • EN ISO 20345:2022

Stainless Steel Toecap is heavy duty and corrosion resistant. The impact resistance can reach 200 joules from falling or rolling objects. The compression resistance can reach 15kN.



#### VortiGard™ Steel Plate Protection • EN ISO 20345:2022

Steel midsole plate is flexible and corrosion resistant. The penetration resistance can reach 1100 newtons from nail or other sharp objects. The flex resistance can reach to 1 X 10<sup>6</sup> flexion cycles without visible cracking.



#### Breathable & Removable Insoles • EN ISO 20347:2022

Removable EVA Insole provides maximum comfort to your feet and long-stand hours, greatly reduce knee and ankle pressure during walking. The insoles are designed with holes, which is breathable & sweat-absorption.



#### Slip Resistant Outsole Design • EN ISO 20345:2022

The outsole is made with PVC material, plus 5-10% nitrile. Ultra grip lug design ensures non-slip traction on different workplaces. High density PVC outsole is designed as EN ISO 20345 standard for tear resistant and abrasion resistant.

### SAFETOE Standard Package Instruction (Average 42# for Reference)

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| Boots Weight : 1.8~1.9 KGS /Pair    | Carton Weight : 19-20 KGS /Carton |
| 1 Pair / Polybag, 10 Pairs / Carton | Carton Dimension : 50×30×50CM     |

#### User Instructions:

- 1.) RECOMMENDED TO USE : Construction, Chemical, Food Industry, Catering, Cleaning, Farm & Garden, Food Storage etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on package. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
- 4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.
- 5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.



**Color Available: Black, Blue, Yellow, White etc**

